

OSO TORQUE SPECS

HARDWARE	TORQUE SPEC <small>(NM)</small>	THREAD TREATMENT / NOTES
MOTOR		
Motor bolts	20	Loctite 243 if no green threadpatch
Motor cover Guard	2	Grease
Motor Bash Guard	2	Grease
Downtube Bash Guard	2	Grease
Upper Battery Mount	12	Grease
Lower Battery Mount	12	Loctite 243
Speed Sensor Cable Clip	2	Grease
Charge Port Exterior Bolts	Barely Tight/ Just Touching	Dry
Battery Door Cover	1/4 turn: left to release, right to latch	None
SUSPENSION		
Forward Shock Mount Bolts	12	Inside of the trunnion mount threads should be treated with Loctite 243 (if no green threadpatch on bolt)
Rear Shock Bolt	10	Titanium Bolts: Ti anti-seize on shaft and threads
LINKAGE		
Top Upper Link Bolt	20	Loctite 243 on threads (if no green threadpatch), grease on flange
Botter Upper Link Bolt	20	Loctite 243 on threads (if no green threadpatch), grease on flange
Lower Link 6mm Side Preload Bolts	3	Loctite 243 on threads (if no green threadpatch), grease on flange
Lower Link 5mm Pinch Bolts	8	Loctite 243
MISC		
Rear Brake Caliper	6	Loctite 243
Seat Binder	7	Grease
Derailleur Hanger Bolt	25	Dry (reverse thread!)
Rear Axle	12	Grease